

Luneburg lens antenna **OLLA-2640**

Luneburg lens antenna is a spherical dielectric lens antenna, which focuses microwaves to the focal point through dielectric. Luneburg lens antenna is widely used in microwave, millimeter wave, mobile communication, satellite communication and radio astronomy due to its high gain, low profile and multi-feed multi-beam operation.

The distribution has sphere symmetry, which makes any point on the Luneberg lens sphere the focal point of the lens sphere. Therefore, as long as the position of the antenna feed on the spherical surface is controlled, the electromagnetic radiation beam can be directed in any direction, and there is no defocus problem as the position of the feed on the spherical surface changes.

Due to the medium distribution characteristics of the lens, the antenna is relatively insensitive to the frequency band of electromagnetic waves, so the frequency band can be very wide.

Customize Luneburg lens antenna are offered for the frequency range of 2 to 110 GHz. The standard gain value and corresponding half power beamwidth at 2.6GHz-3.95GHz is 15 dBi and 30 degrees.

Other gain values are available as custom order. The 3D printed antenna can be connected to standard waveguide interface. Other customized feeds are also available.



PRODUCT DIMENSIONS

145mm

All-dielectric		
Light weight		
Low cost		
Low side lobe		
Easy configuration		
Customized design		

Applications

Features

Antenna reference

Radiation element for sub-systems	
Antenna mounted on S-band waveguide	

Electrical Specifications

Frequency Range(GHz)	(2.6-3.95)GHz
Gain(dB)	15 dBi
Return Loss (dB)	< -20 dB
Beamwidth	30 degree@3.3GHz
Polarization type	All polarizations
Sidelobe Leve	-20 dB
Diameter dimensions	145mm
Antenna weight	116 g

Antenna weight



GAIN



EC Microwave is trademark of Ocean Microwave All rights of respective trademark owners reserved. © EC Microwave 2017

www.rfecho.com



